

FIRE EXTINGUISHER



ISO 9001
Quality
Management
Systems
CERTIFIED

ISO 14001
Environmental
Management
CERTIFIED

ISO 45001
Occupational
Health and Safety
Management
CERTIFIED



TIS. 332-2537

FIRE EXTINGUISHER



DRY CHEMICAL

| MODEL | FL 5 | FL 10 | FL 15 |
|---------------------|----------|---------------------------|---------------------------|
| DESCRIPTION | 5 LBS | 10 LBS | 15 LBS |
| Weight of Chemical | 2.5 Kg. | 4.5 Kg. | 6.8 Kg. |
| Weight of Container | 2.1 Kg. | 3.1 Kg. | 3.6 Kg. |
| Gross Weight | 4.6 Kg. | 7.6 Kg. | 10.4 Kg. |
| Overall Height | 15 " | 20 " | 21.5 " |
| Shell Diameter | 4.5 " | 5.5 " | 6 " |
| Working Pressure | 195 PSI | 195 PSI | 195 PSI |
| Test Pressure | 500 PSI | 500 PSI | 500 PSI |
| Burst Pressure | 1000 PSI | 1000 PSI | 1000 PSI |
| Temperature | 27+2 °C | 27+2 °C | 27+2 °C |
| Discharging Time | 12 Sec. | 14 Sec. | 20 Sec. |
| Shooting Range | 4-6 m. | 6-8 m. | 8-10 m. |
| Propellant Gas | N2 Gas | N2 Gas | N2 Gas |
| Type of Chemical | A,B,C | A,B,C | A,B,C |
| Cylinder Material | Steel | Steel | Steel |
| Fire Rating | 2A:2B | 2A:2B 6A:10B 6A:20B | 2A:2B 6A:10B 6A:20B |



CARBON DIOXIDE

| | | |
|--------------------|----------|----------|
| MODEL | FLCO 10 | FLCO 15 |
| DESCRIPTION | 10 LBS | 15 LBS |
| Capacity | 4.5 Kg. | 6.8 Kg. |
| Gross Weight | 13.5 Kg. | 19 Kg. |
| Overall Height | 60 cm. | 83 cm. |
| Shell Diameter | 15.2 cm. | 15.2 cm. |
| Working Pressure | 150 Bar | 150 Bar |
| Test Pressure | 350 Bar | 350 Bar |
| Discharging Time | 16 sec. | 20 sec. |
| Shooting Range | 4.5 m. | 4.5 m. |
| Cylinder Material | CK45 | CK45 |
| Cylinder Thickness | 5 mm. | 5 mm. |



CLEAN AGENT

| | | |
|---------------------|--------------|--------------|
| MODEL | FLCA 10 | FLCA 15 |
| DESCRIPTION | 10 LBS | 15 LBS |
| Weight of Chemical | 4.6 Kg. | 6.8 Kg. |
| Weight of Container | 2.7 Kg. | 2.8 Kg. |
| Gross Weight | 7.3 Kg. | 9.6 Kg. |
| Overall Height | 20.0 " | 21.5 " |
| Shell Diameter | 5.5 " | 6.0 " |
| Working Pressure | 195 PSI | 195 PSI |
| Test Pressure | 500 PSI | 500 PSI |
| Burst Pressure | 1000 PSI | 1000 PSI |
| Temperature | -20 to 60 °C | -20 to 60 °C |
| Discharging Time | 12-20 Sec. | 14-25 Sec. |
| Shooting Range | 4-6 m. | 4-6 m. |
| Type of Chemical | HFCs Agent | HFCs Agent |
| Fire Rating | 1A-1B | 1A-1B |

FIRE LINE DO NOT CROSS